

#BringTheRevolution

# 1340 R

SKID STEER LOADER



Engine  
Yanmar 4TNV88

Rated Operating Load  
612 kg (1340 lb)

 **MANITOU**  
HANDLING YOUR WORLD



# Designed For Performance

Offers enhanced performance in loading, grading and digging below grade applications. Due to the radial lift path, the maximum reach is greater at the middle of the lift height.

## **Rated operating capacity**

Standard: 612 kg

Overall height  
**1826 mm**

Lifting height  
**2794 mm**

Operating capacity  
**612 kg**



### **Yanmar Tier III Engine**

Powerful Yanmar Tier III 4-cylinder naturally aspirated Diesel Engine [Yanmar 4TNV88]



### **Easy transport**

With an operating weight of only 2200 kg, the 1340 R can be easily towed on a trailer behind a standard truck



### **Level I ROPS/FOPS**

Level I FOPS are standard, which provides added levels of protection for the operator.

### **FRONT DOOR**

Front Door as Standard Fitment

### **EASY ACCESS TO ENGINE**

Large Rear Engine cover with hinged rear door

### **POWER BOOM**

Low-profile boom design offers optimal side-to-side visibility.

### **EASY ENTRY EXIT**

Dual grab handles

### **EXCELLENT FORWARD REACH**

1340 R provides excellent forward reach at the middle of the lift path. This provides excellent performance for loading flatbed trucks backfilling or dumping over a wall.



### **COMPACT AND SAFE**

Designed to work in compact spaces. Safety features that protects your machine and operator



# Comfort & Operator safety

- **Visibility**

Wide opening in the front of the machine and large screen windows provide high visibility for increased safety and precise load placement.

- **Operator Presence**

The machine safety system allows operation only when the user is on the seat and the restraint bar is lowered into position.

- **Easy entry and exit**

Large entry area allows for easy access to the operator station.

- **Hydraloc**

Automatic interlock system locks lift, tilt & drive systems when the operator leaves the seat, increasing operator safety.



## Excellent views from all sides for safety and precise operation

Excellent visibility to the front, sides and rear of the machine allow for precise placement of loads and reduced jobsite incidents. A highmounted seat provides an excellent vantage point to the attachment and cutting edge.

## 1340 R SKID STEER LOADER

# Get attached

Manitou Skid loaders offer an exceptional balance of power and maneuverability, and they can adapt to nearly any task with a wide range of attachments available.

**Pallet Fork**



**Rock breaker**



**Sweeper Collector**



**Multi Purpose Bucket**



**Auger with Mount**



**Backhoe attachment**



**Bucket with Grab**



**Muck Fork**



**Dozer blade**



add many more....

# Technical Specifications

Capacities		Metric
Rated Operating Capacity		612 kg
Operating Weight - Approximate		2200 kg
Tipping capacity		1224 kg
Weight and dimensions		Metric
Overall Operating Height - Fully Raised mm (in)	A	3584 (141.1)
Height to Hinge Pin – Fully Raised mm (in)	B	2794 (110)
Overall Height to Top of Rops mm (in)	C	1826 (71.8)
Dump angle at full height	D	42 °
Dump height mm (in)	E	2197 (86.4)
Overall length with bucket mm (in)	F	2952 (116.2)
Dump reach at full height mm (in)	G	528 (20.7)
Rollback at ground	H	29 °
Rollback Angle at full Height	I	99 °
Seat to ground height mm (in)	J	853 (33.6)
Wheelbase mm (in)	K	923 (36.3)
Overall width less bucket mm (in)	L	1346 (53)
Bucket Width mm (in)	M	1562 (61.5)
Ground clearance mm (in)	N	211 (8.3)
Overall length - Less Bucket mm (in)	O	2314 (91.1)
Departure angle	P	29 °
Clearance Radius - Front with Bucket mm (in)	Q	1758 (69.2)
Clearance Circle - Front without Bucket mm (in)	R	1102 (43.4)
Clearance Circle - Rear mm (in)	S	1484 (58.4)
Performances		Metric
Travel speed (unladen)		10.70 km/h
Wheels		Metric
Standard tyres		10X 16.5 - 10 PR Heavy Duty
Transmission type		Fully hydrostatic
Number of drive wheels		4

Follow Us @



Effective Date: Feb, 2022. All dimensions, weights & timings are variable within 1.5%. Company reserves the right to change specifications without prior notice. The illustration do not necessarily show the standard version of the machine. Product specifications & prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instruction on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product & sale & we make no other warranty, express or implied.






**Manitou South Asia Pvt. Ltd.**

Regd. Office: 1st Floor, Plot No. A-10, Block-B1, Main Mathura Road, Mohan Co-op Indl. Estate, New Delhi - 110044  
Tel.: 011- 407 42701 E-mail: info.mind@manitou-group.com Web: www.manitou.com

## 1340 R SKID STEER LOADER

Engine		Metric
Engine brand		Yanmar
Engine model		4TNV88
Engine norm		BS-III
Gross Power (HP)		49 HP
Max. torque / Engine rotation		142 Nm / 1600 rpm
Battery		12 V
Starter (kw)		3 kW
Hydraulics		Metric
Auxiliary Hydraulic Pressure		190 bar
Hydraulic Flow		62 LPM
Tank capacities		Metric
Fuel tank		47 l
Displacement		2.20 l
Reservoir Capacity Hydraulics		30.30 l
Coolant system capacity		7.60 l
LH Chain case		8.25 l
RH Chain case		8.25 l
Standard Fitment		
Front Door		
Backup Alarm		
Options Available		
Solid Flex tyres		
Easy Manager		

### Dimensional Drawing



Your dealer:



**1800 103 7600**