

RANGE

**MC**



Scan and discover  
more information  
on [manitou.com](https://manitou.com)

 **MANITOU**  
HANDLING YOUR WORLD




## Your total cost of ownership (TCO)

From the design stage, we take your total cost of ownership into account in order to develop high-performance, robust and cost-optimised machines.

- **Reduced consumption and noise on site**  
Reduced cabin noise and fuel consumption with the new Stage 5 engine.  
Significant environmental impact.
- **Easy maintenance**  
Simplified access to maintenance components for reducing machine downtime.  
Increased maintenance intervals.
- **Optimised resale value**  
The MC range brings you high resale value thanks to its performance, quality and robustness of its components.
- **Mast robustness**  
Designed for rough terrain **fixed** directly to the chassis to avoid mast torsion.

### Switch 2/4 wheel drive

This allows the operator to reduce fuel consumption by up to 12%, increase travelling speed and minimise wear and tear on rear tyres.



## Your performance, our priority

Tough enough for any challenge!


- **Hydrostatic transmission**  
Recommended for applications requiring:
  - regulated working power,
  - constant speed control,
  - precision in driving and approach,
  - repetitive braking: the automatic braking on release of the pedal improves driving comfort for the operator.
- **Exceptional gradeability**  
Equipped with large diameter front wheels for good weight distribution on the axles and central differential locking system, the machines in this range offer very good performance.
- **Rough-terrain mast design**  
Its width ensures better stability of the truck for greater safety when handling long or bulky loads.  
Mast tilting up to 12°.
- **Turning radius**  
The MC machine, with a turning radius from 2.58 m, can meet the challenges of narrow storage areas and construction sites.
- **Rough-terrain design**  
An important **ground clearance** of 30 cm.  
An **oscillating rear axle** with a high degree of articulation



## Your Connected solution

Monitor the position of your machine 24 hours a day in real time and optimise its operational follow-up.

- **View in real time**  
Manage your fleet remotely and benefit from a wealth of information about your machines accessible on your computer, tablet or smartphone.
- **Anticipate maintenance**  
Save time : share your alerts directly with the technician to anticipate visits and reduce response time.
- **Analyse performance**  
View the performance of your machines in a graphical format that is easy to follow and interpret.



### Protect your equipment and control access

As an option, you can manage driving authorisations and control operator access to your machines. You ensure their safety in and around the machine.



### Need more compactness? Choose the Buggy cab

As an option, you have access to the buggy version:  
Lower cab height of 1990 m

## Your compactness & comfort

No compromise on safety and efficiency!

Comfort and visibility are among the major points on selecting your truck. MC is unparalleled on both:

- Large cab, with seat in the middle
- Wide windscreen and roof glass with best visibility on the market.
- Options for pneumatic seat
- Most silent truck on the market with double skinned engine hood
- Large and safe access to the cab with the floor
- Highest ground clearance on the market



Maximum lifting height :  
**up to 5500 mm**

Maximum capacity :  
**3500 kg**

Cabin height from  
**1990 mm**

**2/4 wheel drive**

**Hydrostatic transmission**

**Maintenance easy  
as 1-2-3**

Maintenance is as easy as using the MC!  
With simple and safe access to all control point and levels, to main components and to greasing points, MC is a very effective truck to check, clean and repair.  
Think this is useless?  
This is twice to five time less than the competition. That is from one to six hours per year...and much safer.



**Panoramic  
cabin roof**

**Comfortable working  
environment**

A remarkable driving experience, making work less tiring and improving productivity with the spacious and suspended cab.  
JSM is optionnally available to have all handling controls in the palm of your hand.

**Curved  
counterweight  
for improved rear  
visibility.**

**Which  
mast  
to choose ?**

First of course the maximal height you need to level your loads to plus a 15 cm margin for safety.

Then your height constraints : what is the lower door I need to cross?

And finally the visibility : FVD and FVT suggest a better visibility at highest height on the load.

On MC18, all our FVD and FLT masts keep their nominal capacity up to a minimum of 3000 mm.

**YOUR SAFETY  
& VISIBILITY**

Visibility is a an essential element in the safety of drivers and their environment, and this key element is factored in at the design stage.

**Easy access**

Upper left hand post, non-slip steps and open space at floor level to keep safety and comfort during the often repetitive activities of getting in and out of the driver's cab.



**Simplified use sheet  
Handling videos**  
Reduce Risks helps you  
to use your machines safely



**JSM advantages**

The JSM (Joystick Switch & Move) is optionnally available on MC range, putting all handling controls in the palm of your hand. And giving you unequaled precision and speed for your daily tasks!








Loading/unloading lorries & containers  
Scrapyards  
Events  
Roadshows...  
Basement construction  
Masonry  
Arboriculture  
Nurseries  
Market gardening  
Oyster farming...


### Versatility & strength for all your jobs

These attachments require three or four hydraulic movements, so allow for levers and distributors fitted up to the attachment mounting system when picking your order.




### Your mast


To meet your height requirements, the MC range offers a number of mast options:



**Full Visibility Duplex (FVD)**  
Two mast components with low free lift. The mobile component is activated when the operator uses the hydraulic lever.



**Free Lift Triplex (FLT)**  
The central cylinder gives the operator greater free lift without having to raise the mast. The mast consists of three elements, which allow for a low overall height while maintaining a significant working height.



**Full Visibility Triplex (FVT)**  
Three mast components without free lift. The mobile component is activated when the operator uses the hydraulic lever, allowing for both low height and good front visibility.

**MC 18 :** FVD 3300 to 4500 / FVT 3300 / FLT 3700 to 5500  
**MC 25/30 :** FVD 3300 to 4500 / FVT 3300 / FLT 3400 to 6000

### Your different tyres

- Rough-terrain: ideal for working on uneven, degraded surfaces.
- Mixed: suitable for moving from a stable surface to a rough-terrain surface (and vice versa).
- Low pressure to reduce the impact on your grassy / sandy ground



Rough-terrain



Mixed



Mixed



Low Pressure

### BENEFITS

An MC truck can go from a width of 1450 mm to 1600 mm with the biggest set of tyres. This reduces marking by the machine and gives greater stability. However, a standard set of tyres allows the compactness of the equipment to be preserved.

Pay attention as this item represents a significant expenditure as part of the total cost of ownership (TCO). Good tyres that are suited to your application will reduce the number of tyre changes and therefore help to optimise the TCO. [for advice.](#)



### Tilting carriage

MC may be fitted as an option with a tilting carriage : a quick and easy way to switch between attachments, making your MC versatile and even more useful!





“

As a fleet manager, we measure precisely the TCO and profitability of our equipment. We look for machines that are versatile and safe, and that meet the space constraints of the construction sector.

Your dealer



Scan and discover  
more information  
on **manitou.com**



This publication describes the versions and configuration possibilities of Manitou products which may differ in equipment. The equipment shown in this brochure may be standard, optional, or not available depending on the version. Manitou reserves the right to change the specifications described and shown at any time without notice. The specifications shown are not binding on the manufacturer. For more details, contact your Manitou dealer. Non contractual document. All logos and corporate identity are the property of Manitou and may not be used without permission. All rights reserved. The photos and diagrams contained in this brochure are provided for reference purposes only. Manitou BF SA - Public

limited company with a Board of Directors - Share capital: 39 547 824 euros - 857 802 508 RCS Nantes

©Manitou ©Adobe stock